



Elegant browns

PANAGET

manufacture française de parquet
DEPUIS 1929



No 1014166

FRENCH OAK AUTHENTIC CUIR, DIVA 184 TONGUE & GROOVE / 14 MM

Characteristics

Species: French oak **Origin:** France

Grading: Authentic - light and dark wood, black knots, filled knots, partially opened knots, discolouration, black marks, cracks. The size of the knots is proportional to the width of the planks.

Finish: Cuir - brushed, old leather-tone matt oiled / Hard wax oil

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation. Please refer to our maintenance guide.

Design

Engineered extra-wide single plank made under the patent EN 13489
Tongue & Groove



Description

Width: 184 mm

Length: 500 to 2000 mm

Thickness: 14 mm

Top layer: 3.4 mm

Core: plywood

Counterbalance: unrolled wood

Profile: 4 bevels

Packing

Sqm/pack: 1.84

Pack/pallet: 44

Sqm/pallet: 80.96

Weight/sqm: 7.4 kg

Weight/pallet: 599.1 kg

Installation method



Floating glued
installation under the
patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Floating installation using
plastic DPM and Isol 20 or fully
glue down using Presto PM



* Emissions of volatile substances which could be toxic if inhaled. These are rated on a scale from A+ (very low) to C (high).



PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com



DECLARATION OF PERFORMANCE

NO 1014166

Unique identification code of the product-type: Diva 184 Tongue & Groove, 14 mm, French oak

Intended use/es: Engineered extra-wide single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction to fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit	
Formaldéhyde emission	E1	
Content of pentachlorophénol	PCP ≤ 5 ppm	
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m ³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.108	
Biological sustainability	Classe 1	EN 335

N/A: Not Applicable

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011. under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 15 november 2019

Carole FRANÇOIS

3 rue d'Orgères - 35230 Bourgbarré - FRANCE / tel: +33 (0)2 99 05 77 77 - fax: +33 (0)2 99 57 73 55

Entreprise dont le système qualité a été **certifié ISO 9001** par Bureau Veritas Certification.

SAS au capital de 4 957 200 € - RCS Rennes B 402 853 220 - Siret : 402 853 220 000 34 - APE : 1622 Z - No TVA : FR 0640 2853220

www.panaget.com