


## Oak Live Pure Animoso

Product details / Technical properties

|                            |                                    |                                     |                    |                                       |               |
|----------------------------|------------------------------------|-------------------------------------|--------------------|---------------------------------------|---------------|
| <b>Article number</b>      | 10152069 / EBG843MD                | <b>Bevel</b>                        | beveled 4V         | <b>Moisture content</b>               | 5-9%          |
| <b>Wood</b>                | Oak                                | <b>Number of slotted top layers</b> | 0                  | <b>Fire protection classification</b> | Dfl-s1        |
| <b>Grading</b>             | Animoso                            | <b>Surface structure</b>            | brushed            | <b>Content of formaldehyde</b>        | E 1           |
| <b>Product type</b>        | 3-layer parquet                    | <b>m² per carton</b>                | 0,95               | <b>PCP content</b>                    | NPD           |
| <b>Format</b>              | 14mm Plank<br>Herringbone, A-Plank | <b>Boards per carton</b>            | 10                 | <b>Brinell Value</b>                  | 38            |
| <b>Dimensions</b>          | 14 x 138 x 690 mm                  | <b>Weight per carton (kg)</b>       | 11                 | <b>Shrinking and swelling</b>         |               |
| <b>Top layer thickness</b> | 3,5 mm                             | <b>m² per pallet</b>                | 46,55              | <b>Breaking strength</b>              | NPD           |
| <b>Core material</b>       | HDF / Spruce                       | <b>Boxes per pallet</b>             | 49                 | <b>Thermal conductivity (W/(m*K))</b> | 0,14          |
| <b>Connection</b>          | 5G Click                           | <b>Weight per pallet (kg)</b>       | 539                | <b>Thermal resistance (m²*K)/W</b>    | 0,1           |
| <b>Floor heating</b>       | suitable                           | <b>EN Norm</b>                      | EN 13489           | <b>Antislip performance (CE)</b>      | USRV 91       |
| <b>Treatment</b>           | Live Pure lacquer                  | <b>FSC claim</b>                    | controlled sources | <b>Antislip performance (DIN)</b>     | R11           |
| <b>Appearance</b>          | Golden floors                      | <b>Performance classification</b>   | Class 1            | <b>Nobb.number</b>                    | 60090261      |
| <b>Colour</b>              |                                    | <b>Density</b>                      | >= 500kg/m³        | <b>EAN Code</b>                       | 7035580218630 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.