

## Oak Vivo Live Pure

## Product details / Technical properties

Article number	10157047 /	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Vivo	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	0,95	PCP content	NPD
Format	Plank 14mm Plank Herringbone	Boards per carton	10	Brinell Value	38
Dimensions	14 x 138 x 690 mm	Weight per carton (kg)	11,5	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	46,55	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K)	0,14
Connection	5G Click	Weight per pallet (kg)	563,5	Thermal resistance (m <sup>2*</sup> K)/W	0,1
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Treatment	Live Pure lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R11
Appearance	Golden floors	Performance classification	Class 1	Nobb.number	60090267
Colour		Density	>= 500kg/m³	EAN Code	7035580225270















The mark of responsible forestry

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

