



Elegant browns No 1016189

FRENCH OAK ZENITUDE ARGILE, **DIVA 184 TONGUE & GROOVE / 14 MM**

Characteristics

Species: French oak Origin: France

Grading: Zenitude - light and dark wood, black knots, filled knots, opened knots, discolouration, cracks, splits, sapwood. Grade with all pecularities of the wood without limitation. The size of the knots is proportional to the width of the planks.

Finish: Argile - brushed, clay-tone matt lacquered / Ecostrong lacquer

Argile is a tint that acts on wood's natural tannin properties to create tan aged finish. In some casesn the shade may change slightly over time.

Design

Engineered extra-wide single plank made under the patent EN 13489 Tongue & Groove







Description

Width: 184 mm

Length: 500 to 2000 mm Thickness: 14 mm Top layer: 3.4 mm Core: plywood

Counterbalance: unrolled wood

Profile: 2 bevels

Packing

Sqm/pack: 1.84 Pack/pallet: 44 Sqm/pallet: 80.96 Weight/sqm: 7.4 kg Weight/pallet: 599.1 kg

Installation method



Floating glued installation under the patent DTU 51.11




Glue down installation under the patent DTU 51.2



Floating installation using plastic DPM and Isol 20 or fully glue down using Presto PM











PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com



DECLARATION OF PERFORMANCE NO 1016189

CE

Unique identification code of the product-type: Diva 184 Tongue & Groove, 14 mm, French oak

Intented use/es: Engineered extra-wide single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No4

Harmonised standard: EN 14342: 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction to fire	Dfl-s1	
Features for this classification:		
- Average minimum density (Kg/m³)	500	EN 14342 : 2013
- Average thickness (mm)	14	
- Intented use, fitting mode	Floating fit	
Formaldéhyde emission	E1	EN 717-1
Content of pentachlorophénol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m².K/W)	0.108	
Biological sustainability	Classe 1	EN 335

N/A: Not Applicate

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011. under the sole responsability of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 15 november 2019

Carole FRANÇOIS

^{*}VOC: Volatile Organic Compounds

^{**}CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category