



## OAK LYNX OILED

Lynx Oiled celebrates oak at its most expressive. Vivid knots and lively color shifts give each plank its own personality. Deep brushing draws out the grain, while a 4-sided micro-bevel frames every board with subtle shadow lines. Larger knot holes are carefully repaired by hand using wooden plugs and filler small signatures of craftsmanship. The natural oil finish sinks into the wood to enrich tone and depth, leaving a soft, low-sheen surface.

PRODUCT DETAILS		PRODU
Product type / Construction	Wood Floors / 3-layer parquet	Hardness
Article Number / EAN Code	131268220 / 7393969306447	range
Design / Wood Species	Plank / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNI
Natural/Stained		Moisture
Design features	Microbevelled 4-sided, Brushed	Minimun
Width x Length x Thickness	187 x 2266 x 13 mm	kg/m <sup>3</sup>
Weight per package / per	24 kg / 7.19 kg	Reaction
m2		Formalde
Area per package / per	3.39 m <sup>2</sup> / 118.65 m <sup>2</sup>	Content
pallet		
Grading	Dynamic	Breaking
Joint	Woodloc® 5G	Thermal
Installation method	Floating, Glue-down	Biologica
Floor heating	Yes	CARB2
Wear leayer material /	Hardwood / 2.6 mm	Slip resis
thickness		Mendicure dans unit settingur
Resandable	2-3 times	A+
Core material	Pine/Spruce	
Backside material	Spruce	

PRODUCT D	ETAILS
-----------	--------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CFN/TS15676	NPD





## **DETAILED DESCRIPTION**

All naturally occurring wood color variations are allowed, ranging from light to dark brown tones. Sapwood may be present. The product features very large sound and black knots, as well as natural cracks. Knot holes and cracks are repaired with a dark filler, and larger openings may be plugged with knot inserts.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.