



FROSTED OAT STRIP

Frosted Oat strip is inspired by late autumn grain fields covered in frost. The soft white and transparent stain allows the rustic wood to enhance the natural design completed with an ultramatt finish.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N6BEKN4KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969048347	Board	3-strip	Minimum Mean Density kg/m³		
Surface treatment	Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles.	Grading	Lively	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Brushed	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
		Collection	Beyond Retro Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
		Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Dimensions	2423 x 200 x 15 mm	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Weight per Package (kg)	23.716 kg	Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)
Area per Package (m²)	2.91 m²	Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Area per pallet (m²)	130.95 m²	Floor heating	Yes	CARB2		
Package info	Packages may contain start and stop boards.	Warranty	30 years	Compliant		
DETAIL DESCRIPTION		Wear-layer material	Hardwood			
		Wear-layer thickness	3.5 mm			
		Core material	Pine/Spruce/Alder			
		Thickness	15 mm			
		Surface Colour	Light white			
		Installation method	Floating, Glue-down			

COLOUR CHANGE

Stained product - noticeable color change over time.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.