

Product quality			
Formats		856 x 403 x 5,5 mm	1290 x 196 x 5,5 mm
Packaging	Pack:	8 elements / 2.76 m ² / 19.44 kg	8 elements / 2.023 m ² / 14.34 kg
	Pallet:	30 packs / 82.792 m ² / 598.14 kg	48 packs / 97.091 m ² / 703.42 kg

Tolerances (Requirement EN 16511:2014+A1:2019)			
Squareness of the elements (≤ 0.50mm)		≤ 0,15 mm	
Determination of Linearity (≤ 0.30 mm/m)		≤ 0,20 mm/m	
Flatness concave / convex	lengthwise (≤ 0.50 / ≤ 1.0 %)	≤ 0,35 / ≤ 1,0 %	
	wide (≤ 0.10 / ≤ 0.15 %)	≤ 0,10 / ≤ 0,15 %	
Surface flushness	(average ≤ 0.15 mm)	(average ≤ 0.10 mm)	
	(max. ≤ 0.20 mm)	(max. ≤ 0.15 mm)	
Opening between installed elements	(average ≤ 0.15 mm)	(average ≤ 0.05 mm)	
	(max. ≤ 0.20 mm)	(max. ≤ 0.10 mm)	

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion
Lifetime	10 Years	- cleaning and maintenance see instructions
		- technical changes reserved



Further certifications
in progress.



Classification			
		Test method	Rating
	Utility class 23 domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
	Utility class 33 commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
	Reaction to fire	EN 13501-1	C _{s1} s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
	Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN 425	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating.	EN 12667	0,033 m ² *K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
	Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	≤ 0,05 ppm
	Acoustical - Impact noise reduction	EN ISO 10140-3	17 dB
	Length- and Square separating force	ISO 24334	lengthwise ≥ 1 KN/m transversely ≥ 1,5 KN/m
	Abrasion	prEN 15468 Annex A	> 7.000 rev.
	Impact resistance	EN 13329 Annex F	≥ 1.800 mm
	Micro scratch resistance	EN 16094	Method A MSR-A2
	Slip resistance on an inclined plane	DIN 51130	Authentic texture, genuine embossed texture, wood texture: R10 / Stone texture: -
	Disposal	EAK-Code-number	17 02 03
	Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).		

Changed:	QMB Parador	File:	20210401_PA_TDS_Modular-ONE_Hydron_EN
Date:	01.04.2021	Latest update at:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.04.2021