



Image represents 1.9m<sup>2</sup>

Finish:	Brushed & Oiled
Size:	14 x 190 x 1820mm

Board Dimensions:	14 x 190 x 1820mm (3mm wear layer)
Grade:	Rustic 'B/C/D (Repaired Knots upto 80mm in grade D + Small Repaired Splits allowed)
Oak origin:	Mixed EU Sources
Profile:	Uniclic
Bevel:	B4 1.2mm 'long & short edge'
Pack Size:	2.0748 M2
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Spruce Core, Pine Back
Oil / Lacquer :	UV Cured Lacquer
Sapwood Allowed:	Yes upto 15%
Adhesive:	E1
Bathroom:	Must never Install in this area
Conservatory:	Yes
Float Install:	Yes - Over Underlay
Guarantee:	25 Years Structural - 1 Year Finish
Under floor heating: Embedded systems	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)
Maintenance:	Elka Lacquer maintenance kit
Installation:	Float over underlay, full stick with Elka flex adhesive

**Colour and grain**

**Colour:**

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream. Dark stain applied to enhance the aged look of the flooring.

**Grain:**

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing

**Variations Within Species And Grades:**

- Considerable variation among boards in colour, grain texture and sapwood.

	RUSTIC	A - Grade	B - Grade 30%	C - Grade 30%	D - Grade 40%	For full grading breakdown - visit <a href="http://www.elkaflooring.co.uk">www.elkaflooring.co.uk</a>
--	--------	-----------	------------------	------------------	------------------	----------------------------------------------------------------------------------------------------------

**INSTALLATION IMPLIES ACCEPTANCE**  
NO WARRANTY WILL BE OFFERED FOR APPEARANCE  
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED.

**Please Note: Real wood flooring is a natural product, what is subject to natural variations. Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.**

Imported and distributed by Unilin Distribution

T: 0844 811 8288

visit our website for full grade specification

[www.elkaflooring.co.uk](http://www.elkaflooring.co.uk)