

OAK CUMIN PLANK

Oak Cumin is a light-grey wood floor, inspired by the subtle tones of cumin, offering a soft and contemporary look. The gentle hues create a calm and refined atmosphere, while the natural wood grain adds depth and character. Perfect for modern interiors with a touch of warmth.

	PRODUCT DETAILS		
Wood Flooring / 3-layer veneer 10 mm	LRV / LRV Std1 / LRV Std2	35 / 2.2 / 4.4	
LTCLRW4004-193 / 7393969304603	Warranty	15 years	
1-strip / Oak			
Ultra matt lacquer / Stained	Emission of formaldehyde		E1
Povollad 4 sided Prushad	Moisture content	EN13183	7%±2%
193 x 1980 x 10 mm	—— Minimun Mean Density —— kg/m³		>800 kg/m³
24.3 kg	Reaction To Fire	EN13501-1	Bfl-s1
2.675 m ² / 133.75 m ²	Formaldehyde Emission	EN717-1	E1
	Content PCP	CEN/TR14823	≤ 5 ppm
Calm	Breaking Strength N/mm ²	EN1533	NPD
Woodloc® 5G		EN12664	0.15 W/mK
Floating, Glue-down			.07 (m2K/W)
Yes			Class 1
Hardwood / 0.6 mm	,	LINSSU-2	Compliant
	CARBZ		Compliant
Not resandable	UNACTION CALLS IN THE DECEMBER INTO DECEMBER IN THE DECEMBER IN THE DECEMBER INTO DECEMBER INTO DECEMBER INTO DECEMBER IN THE		
HDF			
Veneer			
	LTCLRW4004-193 / 7393969304603 1-strip / Oak Ultra matt lacquer / Stained Bevelled 4-sided, Brushed 193 x 1980 x 10 mm 24.3 kg 2.675 m² / 133.75 m² Calm Woodloc® 5G Floating, Glue-down Yes Hardwood / 0.6 mm Not resandable HDF	Wood Flooring / 3-layer veneer 10 mmLRV / LRV Std1 / LRV Std2LTCLRW4004-193 / 7393969304603Warranty1-strip / OakTECHNICAL PROPERTIESUltra matt lacquer / StainedEmission of formaldehydeBevelled 4-sided, BrushedMoisture content193 x 1980 x 10 mmkg/m³24.3 kgReaction To Fire2.675 m² / 133.75 m²Formaldehyde EmissionCalmContent PCPVoodloc® 5GBreaking Strength N/mm²Floating, Glue-downThermal Resistance R-ValueYesBiological DurabilityHardwood / 0.6 mmCARB2Not resandableMDF	Wood Flooring / 3-layer veneer 10 mmLRV / LRV Std1 / LRV Std235 / 2.2 / 4.4LTCLRW4004-193 / 7393969304603Warranty15 years1-strip / OakTECHNICAL PROPERTIESUltra matt lacquer / StainedMoisture contentEN13183Bevelled 4-sided, BrushedMoisture contentEN13183193 x 1980 x 10 mmKg/m³Reaction To FireEN13501-12.675 m² / 133.75 m²Reaction To FireEN13501-1CalmContent PCPCEN/TR14823Woodloc@ 5GThermal ConductivityEN1533Floating, Glue-downThermal Resistance R-ValueBiological DurabilityYesBiological DurabilityEN350-2Hardwood / 0.6 mmCARB2CARB2

DETAILED DESCRIPTION

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: The colour matures over time

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Oak Pepper Plank









Oak Cardamom Plank



Oak Cumin Plank



Oak Cloves Plank

Oak Ginger Plank

Oak Nutmeg Plank